Cable Tie Screw Mount

Description

Arvi cable tie accessories are manufactured to the highest quality and tested to the limit. This accessory can be screw-fixed and serves as $\boldsymbol{\alpha}$ mounting base for securing cable ties.

Available Certifications





Features









Product Specifications

PROPERTY	VALUE			
Material	Polyamide 6.6			
Flammability Rating	UL94 V2			
Moisture Absorption	2.7 % – 2.8 % (23 °C, 50 % RH)			
Minimum Installation Temp.	-10 °C			
Operating Temperature	-40 °C to +85 °C			
Max. Short-Term Temp.	+110 °C			
Color	Natural			

Technical Drawing









Cable Tie Screw Mount



Product Specifications

CODE	REFERENCE	C LENGTH (mm)	L WIDTH (mm)	A HEIGHT (mm)	D DIAMETER (mm)	RECOMMENDED SCREW	RECOMMENDED TIE WIDTH (mm)
7021011509	PV-15.00x9.65-N	15,0	9,7	6,9	7,1	M3	3,6
7021011712	PV-17.80x12.70-N	17,8	12,7	8,2	7,1	М3	4,8
7021012216	PV-22.30x16.00-N	22,3	16,0	9,7	8,1	M4	7,6
7021012217	PV-22.30x16.00S-N	22,3	16,0	9,7	10,1	M5	7,6
7021012516	PV-25.40x16.00-N	25,4	16,0	10,8	10,1	M5	9,0

Product Packaging





Logistics Information

			BAG			вох			
CODE	REFERENCE	EAN CODE	QUANTITY (pcs)	DIMENSIONS (cm)	WEIGHT (kg)	QUANTITY (pcs)	DIMENSIONS (mm)	WEIGHT (kg)	
7021011509	PV-15.00x9.65-N	5608445031280	100	9,5x21,0	0,09	15000	55,0x40,0x21,0	14,00	
7021011712	PV-17.80x12.70-N	5608445031297	100	11,5x24,0	0,09	10000	55,0x40,0x15,0	8,00	
7021012216	PV-22.30x16.00-N	5608445031303	100	14,0x21,0	0,02	5000	55,0x40,0x17,0	11,50	
7021012217	PV-22.30x16.00S-N	5608445031310	100	14,0x21,0	0,02	5000	55,0x40,0x21,0	11,80	
7021012516	PV-25.40x16.00-N	5608445031327	100	14,0x28,0	0,02	5000	55,0x40,0x24,0	13,00	