Manga de Tracción con un Ojal

Descripción

Las mangas de tracción de Arvi están fabricadas en acero galvanizado y son altamente flexibles, garantizando un arrastre eficiente para todo tipo de



Especificaciones del Producto

Ø CABLE (mm)	Ø HILO (mm)	Nº HILOS	Ø OJAL (mm)	N° EXTREMOS	LONGITUD (mm)	CARGA DE ROTURA (kg)
10-15	1,25	2	5	4	600	1500
15-20	1,50	2	6	5	600	2500
20-30	1,50	2	6	0	900	3000
30-40	1,50	2	6	6	1250	3000
40-50	2,00	2	8	6	1250	6000
50-65	2,00	2	8	6	1250	6000
65-80	2,00	2	10	8	1250	8000
80-95	2,00	2	10	8	1500	8000
95-110	2,00	2	10	10	1500	10000
110-130	2,00	2	10	10	1500	10000
130-150	2,00	2	12	12	1500	12000





Manga de Tracción con un Ojal



Información Logística

CÓDIGO	REFERENCIA	Ø CABLE (mm)	PESO UNITARIO (kg)	MÚLTIPLO DE VENTA (ud)
7071001511	MT1O-1015	10-15	0,45	
7071002011	MT1O-1520	15-20	0,45	
7071003021	MT1O-2030	20-30	0,59	
7071004031	MT1O-3040	30-40	0,75	
7071005031	MT1O-4050	40-50	0,75	
7071006531	MT1O-5065	50-65	0,75	1
7071008031	MT1O-6580	65-80	0,75	
7071009541	MT1O-8095	80-95	0,89	
7071011041	MT1O-95110	95-110	0,89	
7071013041	MT1O-110130	110-130	0,89	
7071015041	MT1O-130150	130-150	0,89	